

Requirements and Compatibility

For user manuals and dimensional drawings, visit the product page resources tab on ni.com.

Last Revised: 2014-11-06 07:15:09.0

Basler scout Cameras

IEEE 1394 (FireWire®) and GigE Vision Cameras



- VGA to 2 MP resolution options with CCD and CMOS sensors
- Capture rate up to 120 fps
- FireWire cameras offer a standardized, cost-effective, bus-powered IEEE 1394b interface capable of up to 800 Mbit/s
- GigE Vision cameras provide up to 1 Gbit/s throughput and up to 100 m cable lengths for maximum flexibility
- 2 optoisolated inputs and 4 optoisolated outputs

Overview

Basler is a leading global manufacturer of digital cameras for industrial applications, medical devices, traffic systems, and the video surveillance market.

Basler scout IEEE 1394b Cameras

Basler scout IEEE 1394b vision cameras offer a proven design with a wide variety of resolutions and speeds. With many scout model options, you can quickly find the right camera for your application.

The IEEE 1394b standard provides good bandwidth and cable lengths as well as industry-wide adoption. Scout cameras using 800 Mbit/s IEEE 1394b can offer maximum performance in terms of frame rate and bit depth compared to cameras limited by the FireWire-a data rate.

Basler scout GigE Vision Cameras

Basler scout GigE Vision cameras feature a proven design with a variety of resolutions and speeds. With many scout model options, you can quickly find the right camera for your application.

GigE Vision is a widely adopted camera interface that takes advantage of standard, inexpensive cables and hardware for easy implementation. The GigE Vision standard offers the most flexibility, with long cable lengths up to 100 m and the ability to connect multiple cameras to a single port using network hubs.

NI-IMAQdx, a high-performance GigE Vision driver (part of NI Vision Acquisition Software), is optimized for Intel Pro 1000 chipsets to help you reduce CPU loads when acquiring from GigE cameras. For the best experience, you can use GigE Vision cameras with the powerful stand-alone NI Embedded Vision System and NI GigE Vision plug-in boards.

[Back to Top](#)

Requirements and Compatibility

Driver Information

- NI-IMAQdx

Software Compatibility

- LabVIEW Vision Development Module
- NI Vision Builder for Automated Inspection

[Back to Top](#)

Application and Technology

IEEE 1394b Camera Specifications

Basler scout Cameras	Resolution (H x V pixels)	Sensor	Sensor Technology	Sensor Size (optical)	Pixel Size (μm)	Frame Rate
scA640-70fm/fc	659 x 494	Sony ICX424	Progressive Scan CCD	1/3 in.	7.4 x 7.4	71
scA640-74fm/fc	659 x 494	Sony ICX414	Progressive Scan CCD	1/2 in.	9.9 x 9.9	74
scA640-120fm/fc	659 x 494	Sony ICX618	Progressive Scan CCD	1/4 in.	5.6 x 5.6	120
scA750-60fm/fc	752 x 480	Aptina MT9V022	Progressive Scan CMOS	1/3 in.	6.0 x 6.0	64
scA780-54fm/fc	782 x 582	Sony ICX415	Progressive Scan CCD	1/2 in.	8.3 x 8.3	58
scA1000-30fm/fc	1034 x 779	Sony ICX204	Progressive Scan CCD	1/3 in.	4.65 x 4.65	30
scA1300-32fm/fc	1296 x 966	Sony ICX445	Progressive Scan CCD	1/3 in.	3.75 x 3.75	33
scA1390-17fm/fc	1392 x 1040	Sony ICX267	Progressive Scan CCD	1/2 in.	4.65 x 4.65	17
scA1400-17fm/fc	1392 x 1040	Sony ICX285	Progressive Scan CCD	2/3 in.	6.45 x 6.45	17
scA1400-30fm/fc	1392 x 1040	Sony ICX285	Progressive Scan CCD	2/3 in.	6.45 x 6.45	30
scA1600-14fm/fc	1628 x 1236	Sony ICX274	Progressive Scan CCD	1/1.8 in.	4.4 x 4.4	14
scA1600-28fm/fc	1628 x 1236	Sony ICX274	Progressive Scan CCD	1/1.8 in.	4.4 x 4.4	28

Additional Specifications for IEEE 1394b Cameras

Mono/Color	Mono/Color
Interface	IEEE 1394b (screw lock possible)
Video Output Format	Mono 8:8 bits/pixel Mono 16:12 bits/pixel YUV 4:2:2:16 bits/pixel average YUV 4:2:2: (YUYV):16 bits/pixel average Raw 8:8 bits/pixel (R, G, or B) Raw 16:12 bits/pixel (R, G, or B) scA750-60fm/fc (8 bits/pixel only)
Synchronization	Via external trigger, via the IEEE 1394 bus, or free run
Exposure Control	Programmable via the 1394 bus
Housing Size (L x W x H)	73.7 mm x 44 mm x 29 mm (without lens adapter)
Housing Size 90° (L x W x H)	97 mm x 44 mm x 41.8 mm (including lens adapter)
Housing Temperature	Up to 50 °C
Lens Mount	C-mount
Digital I/O	2 optoisolated input ports, 4 optoisolated output ports
Power Requirements	8 to 36 VDC; provided via the IEEE 1394 cable; <1% ripple
Conformity	CE, FCC, DCAM, RoHS, IP 30

GigE Vision Camera Specifications

Basler scout Cameras	Resolution (H x V pixels)	Sensor	Sensor Technology	Sensor Size (optical)	Pixel Size (μm)	Frame Rate
scA640-70gm/gc	659 x 494	Sony ICX424	Progressive Scan CCD	1/3 in.	7.4 x 7.4	70
scA640-74gm/gc	659 x 494	Sony ICX414	Progressive Scan CCD	1/2 in.	9.9 x 9.9	79
scA640-120gm/gc	659 x 494	Sony ICX618	Progressive Scan CCD	1/4 in.	5.6 x 5.6	122
scA750-60gm/gc	752 x 480	Aptina MT9V022	Progressive Scan CMOS	1/3 in.	6.0 x 6.0	64
scA780-54gm/gc	782 x 582	Sony ICX415	Progressive Scan CCD	1/2 in.	8.3 x 8.3	55
scA1000-30gm/gc	1034 x 779	Sony ICX204	Progressive Scan CCD	1/3 in.	4.65 x 4.65	31
scA1300-32gm/gc	1296 x 966	Sony ICX445	Progressive Scan CCD	1/3 in.	3.75 x 3.75	32

scA1390-17gm/gc	1392 x 1040	Sony ICX267	Progressive Scan CCD	1/2 in.	4.65 x 4.65	17
scA1400-17gm/gc	1392 x 1040	Sony ICX285	Progressive Scan CCD	2/3 in.	6.45 x 6.45	17
scA1400-30gm/gc	1392 x 1040	Sony ICX285	Progressive Scan CCD	2/3 in.	6.45 x 6.45	30
scA1600-14gm/gc	1628 x 1236	Sony ICX274	Progressive Scan CCD	1/1.8 in.	4.4 x 4.4	14
scA1600-28gm/gc	1628 x 1236	Sony ICX274	Progressive Scan CCD	1/1.8 in.	4.4 x 4.4	28

Additional Specifications for GigE Vision Cameras

Mono/Color	Mono/Color
Interface	Gigabit Ethernet (screw lock possible)
Video Output Format	Mono 8:8 bits/pixel Mono 16:12 bits/pixel YUV 4:2:2:16 bits/pixel average YUV 4:2:2: (YUYV):16 bits/pixel average Raw 8:8 bits/pixel (R, G, or B) Raw 16:12 bits/pixel (R, G, or B) scA750-60gm/gc (8 bits/pixel only)
Synchronization	Via external trigger or free run
Exposure Control	Programmable via GigE Vision (camera API)
Housing Size (L x W x H)	73.7 mm x 44 mm x 29 mm (without lens adapter)
Housing Size 90° (L x W x H)	97 mm x 44 mm x 41.8 mm (including lens adapter)
Housing Temperature	Up to 50 °C
Lens Mount	C-mount
Digital I/O	2 optoisolated input ports, 4 optoisolated output ports
Power Requirements	12 to 24 V; via Hirose 12-pin connector (max. 10 m cable length)
Conformity	CE, FCC, RoHS, IP 30, GigE Vision, GenICam

[Back to Top](#)

Support and Services

System Assurance Programs

NI system assurance programs are designed to make it even easier for you to own an NI system. These programs include configuration and deployment services for your NI PXI, CompactRIO, or Compact FieldPoint system. The NI Basic System Assurance Program provides a simple integration test and ensures that your system is delivered completely assembled in one box. When you configure your system with the NI Standard System Assurance Program, you can select from available NI system driver sets and application development environments to create customized, reorderable software configurations. Your system arrives fully assembled and tested in one box with your software preinstalled. When you order your system with the standard program, you also receive system-specific documentation including a bill of materials, an integration test report, a recommended maintenance plan, and frequently asked question documents. Finally, the standard program reduces the total cost of owning an NI system by providing three years of warranty coverage and calibration service. Use the online product advisors at ni.com/advisor to find a system assurance program to meet your needs.

Calibration

NI measurement hardware is calibrated to ensure measurement accuracy and verify that the device meets its published specifications. To ensure the ongoing accuracy of your measurement hardware, NI offers basic or detailed recalibration service that provides ongoing ISO 9001 audit compliance and confidence in your measurements. To learn more about NI calibration services or to locate a qualified service center near you, contact your local sales office or visit ni.com/calibration.

Technical Support

Get answers to your technical questions using the following National Instruments resources.

- **Support** - Visit ni.com/support to access the NI KnowledgeBase, example programs, and tutorials or to contact our applications engineers who are located in NI sales offices around the world and speak the local language.
- **Discussion Forums** - Visit forums.ni.com for a diverse set of discussion boards on topics you care about.
- **Online Community** - Visit community.ni.com to find, contribute, or collaborate on customer-contributed technical content with users like you.

Repair

While you may never need your hardware repaired, NI understands that unexpected events may lead to necessary repairs. NI offers repair services performed by highly trained technicians who quickly return your device with the guarantee that it will perform to factory specifications. For more information, visit ni.com/repair.

Training and Certifications

The NI training and certification program delivers the fastest, most certain route to increased proficiency and productivity using NI software and hardware. Training builds the skills to more efficiently develop robust, maintainable applications, while certification validates your knowledge and ability.

- **Classroom training in cities worldwide** - the most comprehensive hands-on training taught by engineers.
- **On-site training at your facility** - an excellent option to train multiple employees at the same time.
- **Online instructor-led training** - lower-cost, remote training if classroom or on-site courses are not possible.
- **Course kits** - lowest-cost, self-paced training that you can use as reference guides.
- **Training memberships** and training credits - to buy now and schedule training later.

Visit ni.com/training for more information.

Extended Warranty

NI offers options for extending the standard product warranty to meet the life-cycle requirements of your project. In addition, because NI understands that your requirements may change, the extended warranty is flexible in length and easily renewed. For more information, visit ni.com/warranty.

OEM

NI offers design-in consulting and product integration assistance if you need NI products for OEM applications. For information about special pricing and services for OEM customers, visit ni.com/oem.

Alliance

Our Professional Services Team is comprised of NI applications engineers, NI Consulting Services, and a worldwide National Instruments Alliance Partner program of more than 700 independent consultants and integrators. Services range from start-up assistance to turnkey system integration. Visit ni.com/alliance.

[Back to Top](#)

©2012 National Instruments. All rights reserved. CompactRIO, FieldPoint, LabVIEW, National Instruments, NI, ni.com, and NI-IMAQ are trademarks of National Instruments. FireWire is a trademark of Apple, Inc., registered in the US and other countries. Other product and company names listed are trademarks or trade names of their respective companies. A National Instruments Alliance Partner is a business entity independent from National Instruments and has no agency, partnership, or joint-venture relationship with National Instruments.

[My Profile](#) | [RSS](#) | [Privacy](#) | [Legal](#) | [Contact NI](#) © 2014 National Instruments Corporation. All rights reserved.