

## INSTALLATION GUIDE

# NI PXI Carrying Case

The NI PXI Carrying Case may be used to transport a 4-, 6-, or 8-slot NI PXI or PXI Express chassis/system, and/or the NI PMA-1115 Portable Monitor Accessory. The case ships with pre-scored open cell polyurethane foam that can be customized to your needs.

## Features

---

- Rugged, watertight design with o-ring seal
- Customizable open cell polyurethane foam
- Retractable pull handle and folding carry handles

## Dimensions

---

Internal .....	54.28 cm × 41.43 cm × 31.90 cm (21.37 in. × 16.31 in. × 12.56 in.)
External .....	63.02 cm × 49.20 cm × 35.23 cm (24.81 in. × 19.37 in. × 13.87 in.)

## What You Need to Get Started

---

- A PXI or PXI Express chassis/system and/or NI PMA-1115 accessory
- An NI PXI Carrying Case
- (Recommended) Toothpicks or similar to mark the outline of the equipment on the foam when determining layout

# Foam Customization Instructions

---

1. Start by placing the equipment on top of the pre-cut foam to determine the proper arrangement.
2. Mark the edges of the foam sections to be removed.
3. Remove each plug in one piece. Be careful not to tear adjacent foam sections.
4. Repeat this procedure for each of the 3 foam layers within the case.



**Tip** If foam sections are damaged or removed unintentionally, they can be reattached with clear rubber cement or spray adhesive. Spray adhesive also can be used to secure customizable foam sections to each other inside the case if desired.

5. Place the equipment in the case to check placement and fit. Items should fit snugly in the foam, and should be removable without damaging the surrounding foam.



**Tip** Leftover foam may be cut to a proper height to elevate smaller equipment for accessibility.